

Y - Standard Geometry
T-A Carbide Drill Blade
Carbide

Diameter Tolerances : -0.0002"/-0.0012"
Thickness Tolerances :

| Material | Imperial Fract. Diam. | Metric Diam. | Imperial Dec. Diam. | Imperial Fract. Thick. | TiN | TiAlN |
|-------------|-----------------------|--------------|---------------------|------------------------|------------|------------|
| C2 (K20) | | 9,50 | 0.3740 | 3/32 | 1C2YT-9.5 | 1C2YA-9.5 |
| | 3/8 | 9,53 | 0.3750 | | 1C2YT-0012 | 1C2YA-0012 |
| | W | 9,80 | 0.3860 | | 1C2YT-.386 | 1C2YA-.386 |
| | 25/64 | 9,92 | 0.3906 | | 1C2YT-.390 | 1C2YA-.390 |
| | | 10,00 | 0.3937 | | 1C2YT-10 | 1C2YA-10 |
| | | 10,20 | 0.4016 | | 1C2YT-10.2 | 1C2YA-10.2 |
| | 13/32 | 10,32 | 0.4063 | | 1C2YT-0013 | 1C2YA-0013 |
| | | 10,50 | 0.4134 | | 1C2YT-10.5 | 1C2YA-10.5 |
| | 27/64 | 10,72 | 0.4219 | | 1C2YT-.421 | 1C2YA-.421 |
| | | 10,80 | 0.4252 | | 1C2YT-10.8 | 1C2YA-10.8 |
| C5 (P40) | | 11,00 | 0.4331 | | 1C2YT-11 | 1C2YA-11 |
| | | 9,50 | 0.3740 | | 1C5YT-9.5 | 1C5YA-9.5 |
| | 3/8 | 9,53 | 0.3750 | | 1C5YT-0012 | 1C5YA-0012 |
| | W | 9,80 | 0.3860 | | 1C5YT-.386 | 1C5YA-.386 |
| | 25/64 | 9,92 | 0.3906 | | 1C5YT-.390 | 1C5YA-.390 |
| | | 10,00 | 0.3937 | | 1C5YT-10 | 1C5YA-10 |
| | | 10,20 | 0.4016 | | 1C5YT-10.2 | 1C5YA-10.2 |
| | 13/32 | 10,32 | 0.4063 | | 1C5YT-0013 | 1C5YA-0013 |
| | | 10,50 | 0.4134 | | 1C5YT-10.5 | 1C5YA-10.5 |
| | 27/64 | 10,72 | 0.4219 | | 1C5YT-.421 | 1C5YA-.421 |
| | 10,80 | 0.4252 | 1C5YT-10.8 | 1C5YA-10.8 | | |
| | 11,00 | 0.4331 | 1C5YT-11 | 1C5YA-11 | | |