



Z - Spot & Chamfer Geometry
T-A (SP) T-A HSS Drill Blade
HSS

Diameter Tolerances : -0.0002”/-0.0012”

Thickness Tolerances :

Material	Imperial Fract. Diam.	Metric Diam.	Imperial Dec. Diam.	Imperial Fract. Thick.	TiN	TiAlN	TiCN
Super Cobalt	7/16	11,11	0.4375	3/32	15ZT-0014-SP	15ZA-0014-SP	15ZN-0014-SP
		11,50	0.4528		15ZT-11.5-SP	15ZA-11.5-SP	15ZN-11.5-SP
	29/64	11,51	0.4531		15ZT-.453-SP	15ZA-.453-SP	15ZN-.453-SP
	15/32	11,91	0.4688		15ZT-0015-SP	15ZA-0015-SP	15ZN-0015-SP
		12,00	0.4724		15ZT-12-SP	15ZA-12-SP	15ZN-12-SP
	31/64	12,30	0.4844		15ZT-.484-SP	15ZA-.484-SP	15ZN-.484-SP
		12,50	0.4921		15ZT-12.5-SP	15ZA-12.5-SP	15ZN-12.5-SP
	1/2	12,70	0.5000		15ZT-0016-SP	15ZA-0016-SP	15ZN-0016-SP