



**0 & 0.5** - Flat Bottom Geometry  
**T-A (FB)** T-A Carbide Drill Blade  
**Carbide**

Diameter Tolerances : **-0.0002"/-0.0012"**  
 Thickness Tolerances :

Material	Imperial Fract. Diam.	Metric Diam.	Imperial Dec. Diam.	Imperial Fract. Thick.	TiN
C2 (K20)		13,00	0.5118	1/8	1C20T-13-FB
	33/64	13,10	0.5156		1C20T-.515-FB
	17/32	13,49	0.5313		1C20T-0017-FB
		13,50	0.5315		1C20T-13.5-FB
	35/64	13,89	0.5469		1C20T-.546-FB
		14,00	0.5512		1C20T-14-FB
	9/16	14,29	0.5625		1C20T-0018-FB
		14,50	0.5709		1C20T-14.5-FB
	37/64	14,68	0.5781		1C20T-.578-FB
		15,00	0.5906		1C20T-15-FB
	19/32	15,08	0.5938		1C20T-0019-FB
	39/64	15,48	0.6094		1C20T-.609-FB
		15,50	0.6102		1C20T-15.5-FB
	5/8	15,88	0.6250		1C20T-0020-FB
		16,00	0.6299		1C20T-16-FB
	41/64	16,27	0.6406		1C20T-.640-FB
		16,50	0.6496		1C20T-16.5-FB
	21/32	16,67	0.6563		1C20T-0021-FB
		17,00	0.6693		1C20T-17-FB
	43/64	17,07	0.6719		1C20T-.671-FB
11/16	17,46	0.6875	1C20T-0022-FB		
	17,50	0.6890	1C20T-17.5-FB		