



0 & 0.5 - Standard Geometry Gen2
Gen2 T-A T-A HSS Drill Blade
HSS

- Lower drilling forces
- Increased drill stability
- Smoother breakout on through holes
- Supplied with AMEC's coating for increased tool life

Diameter Tolerances : **-0.0002"/-0.0012"**

Thickness Tolerances :

- Improved chip formation

Material	Imperial Fract. Diam.	Metric Diam.	Imperial Dec. Diam.	Imperial Fract. Thick.	AM200
Super Cobalt		13,00	0.5118	1/8	450H-13
	33/64	13,10	0.5156		450H-.515
	17/32	13,49	0.5313		450H-0017
		13,50	0.5315		450H-13.5
	35/64	13,89	0.5469		450H-.54
		14,00	0.5512		450H-14
	9/16	14,29	0.5625		450H-0018
		14,50	0.5709		450H-14.5
	37/64	14,68	0.5781		450H-.578
		15,00	0.5906		450H-15
	19/32	15,08	0.5938		450H-0019
	39/64	15,48	0.6094		450H-.609
		15,50	0.6102		450H-15.5
	5/8	15,88	0.6250		450H-0020
		16,00	0.6299		450H-16
	41/64	16,27	0.6406		450H-.640
		16,50	0.6496		450H-16.5
	21/32	16,67	0.6563		450H-0021
		17,00	0.6693		450H-17
	43/64	17,07	0.6719		450H-.671
11/16	17,46	0.6875	450H-0022		
	17,50	0.6890	450H-17.5		