



**0 & 0.5** - Spot & Chamfer Geometry  
**T-A (SP)** T-A HSS Drill Blade  
**HSS**

Diameter Tolerances : **-0.0002"/-0.0012"**  
 Thickness Tolerances :

Material	Imperial Fract. Diam.	Metric Diam.	Imperial Dec. Diam.	Imperial Fract. Thick.	TiN	TiAlN	TiCN
Super Cobalt		13,00	0.5118	1/8	150T-13-SP	150A-13-SP	150N-13-SP
	33/64	13,10	0.5156		150T-.515-SP	150A-.515-SP	150N-.515-SP
	17/32	13,49	0.5313		150T-0017-SP	150A-0017-SP	150N-0017-SP
		13,50	0.5315		150T-13.5-SP	150A-13.5-SP	150N-13.5-SP
	35/64	13,89	0.5469		150T-.546-SP	150A-.546-SP	150N-.546-SP
		14,00	0.5512		150T-14-SP	150A-14-SP	150N-14-SP
	9/16	14,29	0.5625		150T-0018-SP	150A-0018-SP	150N-0018-SP
		14,50	0.5709		150T-14.5-SP	150A-14.5-SP	150N-14.5-SP
	37/64	14,68	0.5781		150T-.578-SP	150A-.578-SP	150N-.578-SP
		15,00	0.5906		150T-15-SP	150A-15-SP	150N-15-SP
	19/32	15,08	0.5938		150T-0019-SP	150A-0019-SP	150N-0019-SP
	39/64	15,48	0.6094		150T-.609-SP	150A-.609-SP	150N-.609-SP
		15,50	0.6102		150T-15.5-SP	150A-15.5-SP	150N-15.5-SP
	5/8	15,88	0.6250		150T-0020-SP	150A-0020-SP	150N-0020-SP
		16,00	0.6299		150T-16-SP	150A-16-SP	150N-16-SP
	41/64	16,27	0.6406		150T-.640-SP	150A-.640-SP	150N-.640-SP
		16,50	0.6496		150T-16.5-SP	150A-16.5-SP	150N-16.5-SP
	21/32	16,67	0.6563		150T-0021-SP	150A-0021-SP	150N-0021-SP
		17,00	0.6693		150T-17-SP	150A-17-SP	150N-17-SP
	43/64	17,07	0.6719		150T-.671-SP	150A-.671-SP	150N-.671-SP
11/16	17,46	0.6875	150T-0022-SP	150A-0022-SP	150N-0022-SP		
	17,50	0.6890	150T-17.5-SP	150A-17.5-SP	150N-17.5-SP		